



BORE	ROD	A	B	C	D	E1 (SOCKET)	E2 (THREAD)	F	G (No. of Holes & Drill Dia.)	H	I	J	K	L	M (No. of Holes & Drill Dia.)	N	P
50	30	233	105	M24x3	24	3/8" BSP	3/8" BSP	110	4~Φ13	135	20	35	160	160x160	4~Φ13	170	20
	40	253	110	M27x2	30	3/8" BSP	3/8" BSP	125	4~Φ13	150	25	35	175	175x175	4~Φ13	185	25
80	50	268	120	M39x2	40	1/2" BSP	1/2" BSP	145	4~Φ13	173	25	40	200	200x200	4~Φ13	215	25
	56	307	135	M42x2	42	1/2" BSP	1/2" BSP	175	6~Φ13	205	25	40	235	235x235	4~Φ13	255	25
100	63	307	135	M42x2	42	1/2" BSP	1/2" BSP	175	6~Φ13	205	25	40	235	235x235	4~Φ13	255	25
	63	314	135	M48x2	48	1/2" BSP	1/2" BSP	190	6~Φ15	225	28	40	260	260x260	4~Φ15	280	28
110	70	314	135	M48x2	48	1/2" BSP	1/2" BSP	190	6~Φ15	225	28	40	260	260x260	4~Φ15	280	28
	70	314	135	M48x2	48	1/2" BSP	1/2" BSP	190	6~Φ15	225	28	40	260	260x260	4~Φ15	280	28
125	70	336	150	M56x2	56	3/4" BSP	3/4" BSP	210	6~Φ17	245	30	45	280	280x280	4~Φ17	305	30
	90	336	150	M56x2	56	3/4" BSP	3/4" BSP	210	6~Φ17	245	30	45	280	280x280	4~Φ17	305	30
150	90	368	158	M64x2	64	3/4" BSP	3/4" BSP	255	8~Φ22	300	35	45	345	345x345	4~Φ22	370	35
	110	368	158	M64x2	64	3/4" BSP	3/4" BSP	255	8~Φ22	300	35	45	345	345x345	4~Φ22	370	35
200	100	430	185	M85x2	85	1" BSP	1" BSP	295	8~Φ22	340	40	50	385	385x385	4~Φ22	420	40
	120	430	185	M85x2	85	1" BSP	1" BSP	295	8~Φ22	340	40	50	385	385x385	4~Φ22	420	40

REAR FLANGE MOUNTING CYLINDER