



BORE	ROD	A	B	C	D	E1 (SOCKET)	E2 (THREAD)	F	G (Self Aligned Bearing ID)	H	I	J	K	L/Thickness of Bearing
50	30	245	105	M24x3	24	3/8" BSP	3/8" BSP	110	25	35	20	35	55	28/20
63	40	263	110	M27x2	30	3/8" BSP	3/8" BSP	125	30	40	25	35	65	30/22
80	50	288	120	M39x2	40	1/2" BSP	1/2" BSP	145	35	50	25	40	75	32/25
100	56	337	135	M42x2	42	1/2" BSP	1/2" BSP	175	40	60	25	40	90	34/28
	63	337	135	M42x2	42	1/2" BSP	1/2" BSP	175	40	60	25	40	90	34/28
110	63	351	135	M48x2	48	1/2" BSP	1/2" BSP	190	50	70	28	40	115	40/35
	70	351	135	M48x2	48	1/2" BSP	1/2" BSP	190	50	70	28	40	115	40/35
125	70	371	150	M56x2	56	3/4" BSP	3/4" BSP	210	50	70	30	45	115	40/35
	90	371	150	M56x2	56	3/4" BSP	3/4" BSP	210	50	70	30	45	115	40/35
150	90	403	158	M64x2	64	3/4" BSP	3/4" BSP	255	60	75	35	45	130	48/44
	110	403	158	M64x2	64	3/4" BSP	3/4" BSP	255	60	75	35	45	130	48/44
200	100	475	185	M85x2	85	1" BSP	1" BSP	295	70	90	40	50	150	52/49
	120	475	185	M85x2	85	1" BSP	1" BSP	295	70	90	40	50	150	52/49