



BORE	ROD	A	B	C	D	E (SOCKET)	F	G (Self Aligned Bearing ID)	H	I	J	K	L (Thickness of Bearing)
50	30	241	47	M24x3	24	3/8" BSP	110	25	35	20	15	55	28/20
63	40	265	55	M27x2	30	3/8" BSP	125	30	50	25	15	65	30/22
80	50	286	55	M39x2	40	1/2" BSP	145	35	50	25	15	70	32/25
100	56	319	60	M42x2	42	1/2" BSP	175	40	60	25	20	90	34/28
	63	319	60	M42x2	42	1/2" BSP	175	40	60	25	20	90	34/28
110	63	351	60	M48x2	48	1/2" BSP	190	50	70	28	25	115	40/35
	70	351	60	M48x2	48	1/2" BSP	190	50	70	28	25	115	40/35
125	70	385	70	M56x2	56	3/4" BSP	210	50	70	30	30	115	40/35
	90	385	70	M56x2	56	3/4" BSP	210	50	70	30	30	115	40/35
	90	418	70	M64x2	64	1" BSP	255	60	75	35	35	130	48/44
150	110	418	70	M64x2	64	1" BSP	255	60	75	35	35	130	48/44
	100	500	85	M85x2	85	1" BSP	295	70	90	40	40	150	52/49
200	120	500	85	M85x2	85	1" BSP	295	70	90	40	40	150	52/49

SPHERICAL BEARING TYPE MOUNTING CYLINDER